

## EARTHMAX SR 31 - Технические спецификации



### Description

EARTHMAX SR 31 - это радиальная шина с цельным металлокордом, специально разработанная для самосвалов с шарнирно-сочлененной рамой и колесных погрузчиков. Залогом прочности и устойчивости этой шины выступают большое количество брекерных слоев с металлокордом, а разнонаправленные жесткие блоки протектора гарантируют им превосходные тяговые характеристики и маневренность даже на грязи. Помимо выдающегося ходового комфорта, шина EARTHMAX SR 31 отличается специальной резиновой смесью протектора, которая наделена исключительной стойкостью к порезам и теплообразованию. Радиальная конструкция способствует снижению сопротивления качению, что положительно сказывается на топливной экономичности транспортных средств.

### UM

US Standard

### Construction



RADIAL

### Machinery

Производство: Бульдозер • Погрузчик

Производство: Шарнирно-сочлененный самосвал •

Бульдозер • Погрузчик

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 25
LI/SS	200 B/208 A2

## Dimensions US Standard

Usa code	94053742
TMPH	185
Overall Width (inch)	30.1
Overall Diameter (inch)	73.3
Static Loaded Radius (inch)	32.2
Rolling Circumference (inch)	218.7
Rim Rec	25.00/3.5
Star Rating	**/*
TRA Code	E3/L3

## Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	25400	26000	27600	28300	30000	30900
5	34200	35300	37500	38600	39700	-

Printed on 19.05.2024 18:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..