

## FL 695 - Загрузить лист технических данных



### Description

Шины FL 695 с уникальным рисунком центральной части протектора специально разработаны для прицепов, применяемых для транспортировки грузов в сферах строительства и сельского хозяйства. Благодаря прочному каркасу шины FL 695 могут выдерживать большие нагрузки, сохраняя стабильность в любых условиях, а глубокий протектор обеспечивает оптимальную самоочистку при движении по дорогам и бездорожью. Множественные слои стального корда защищают эти шины от проколов. Рекомендуется использовать усиленные ободья.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Сельское хозяйство: Прицеп

Производство: Прицеп

SIZE	Version	USACode	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
<b>600/55 R 26.5</b>	STEEL BELTED	94072897	173 D			AG20.00		23.3	52.6	24.4	161	TL	E11-106R-007937
<b>650/55 R 26.5</b>	STEEL BELTED	94067886	178 D			AG20.00	AG22.00	24.8	54.7	24.8	167	TL	E11-106R-007052
<b>600/60 R 30.5</b>	STEEL BELTED	94073832	179 D	179 D	179 D	AG20.00		24.1	58.9	27.3	180.6	TL	E11-106R-008503
<b>710/50 R 30.5</b>	STEEL BELTED	94074082	177 D	177 D	177 D	AG24.00	AG20.00	27.6	58.7	27.2	179.3	TL	E11-106R-008661

Printed on 19.05.2024 18:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..