

XL GRIP (BHL) - Технические спецификации



Description

Шина XL GRIP (BHL) специально разработана для экскаваторов-погрузчиков, работающих с тяжелыми грузами при выполнении экскаваторных, бульдозерных и погрузочных работах. Ненаправленный рисунок протектора обеспечивает лучшую тягу и устойчивость. Специальная резиновая смесь протектора гарантирует превосходные качества по сопротивлению порезам и разрывам, а также длительный срок службы.

UM

US Standard

Construction

 BIAS

Machinery

Производство: экскаватор-погрузчик

Version	ARAMID BELTED
Type	TT
Tyre Size	10.00 - 20

Dimensions US Standard

Usa code	94048915
Ply Rating	18
Overall Width (inch)	11.2
Overall Diameter (inch)	42.3
Static Loaded Radius (inch)	19.9
Rolling Circumference (inch)	128.2
Rim Rec	7.5
Rim Alt	7.0

Load capacity (lbs)

mph / psi	120	110
5	9880	-
25	-	7290

Printed on 19.05.2024 5:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..