

AGRIMAX FORCE - Tekniska specifikationer



Description

AGRIMAX FORCE, BKT:s mest exklusiva produkt, är ett radialdäck specialkonstruerat för jordbearbetning, transport- och skördarbeten med kraftfulla traktorer och skördemaskiner och banar väg för förstklassig prestanda och effektivitet. Tack vare IF-teknologin har däckets hög lastkapacitet med lägre ringtryck jämfört med ett standarddäck och ger minskad jordpackning. AGRIMAX FORCE har förstärkt vulst och erbjuder utökad dragförmåga, imponerande självrensande egenskaper och bränsleekonomi – den bekväma körupplevelsen får du på köpet.

UM

International Standard

Construction

 RADIAL

Machinery

Lantbruk: Skördemaskin • Motorstark traktor

| | |
|-----------|--------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | IF 710/75 R 42 CFO |
| LI/SS | 181 D |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Section Width (mm) | 716 |
| Overall Diameter (mm) | 2133 |
| Static Loaded Radius (mm) | 967 |
| Rolling Circumference (mm) | 6403 |
| SRI (mm) | 1000 |
| Rim Rec | DW 25 B |
| Rim Alt | DW 23 B |
| ECE | E11-106R-006490 |
| TRA Code | R1W |

Load capacity (Kg)

| km/h / bar | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|---------------|------|------|------|------|-------|-------|-------|-------|
| 70 | 3525 | 4050 | 4650 | 5255 | 5855 | 6455 | 7055 | 7505 |
| From 65 to 40 | 3875 | 4455 | 5115 | 5775 | 6435 | 7095 | 7755 | 8250 |
| 30 | 4030 | 4630 | 5315 | 6005 | 6690 | 7375 | 8065 | 8580 |
| 20 | 4185 | 4810 | 5520 | 6235 | 6945 | 7660 | 8375 | 8910 |
| 10 | 4920 | 5655 | 6495 | 7330 | 8170 | 9010 | 9845 | 10475 |
| Upto 30 Cyc | 5035 | 5790 | 6645 | 7505 | 8365 | 9220 | 10080 | 10725 |
| Upto 15 Cyc | 6005 | 6905 | 7925 | 8950 | 9970 | 10995 | 12020 | 12785 |
| Upto 10 Cyc | 6585 | 7570 | 8695 | 9815 | 10935 | 12060 | 13180 | 14025 |
| 10 HT | 4030 | 4630 | 5315 | 6005 | 6690 | 7375 | 8065 | 8580 |

Printed on 5/19/2024 6:18 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..