

## AGRIMAX RT 600 - Tekniska specifikationer

### Description

AGRIMAX RT 600 är ett idealiskt däck för gräsmark, skörde- och spridningsarbeten. Den stora kontaktytan hos AGRIMAX RT 600 säkerställer utmärkt tryckfördelning mot marken, minskar skadorna på gräsmark och skyddar marken. Tack vare tekniken med rundad däckskuldra, förstärkt vulst och fler däckklackar uppnås fantastisk stabilitet och dragförmåga.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Skördemaskin • Spridare • Traktor



|           |                     |
|-----------|---------------------|
| Version   | STEEL BELTED        |
| Type      | TL                  |
| Tyre Size | IF 1250/50 R 32 CFO |
| LI/SS     | 201 B               |

## Dimensions International Standard

|                            |                        |
|----------------------------|------------------------|
| Section Width (mm)         | 1247                   |
| Overall Diameter (mm)      | 2063                   |
| Static Loaded Radius (mm)  | 897                    |
| Rolling Circumference (mm) | 6136                   |
| SRI (mm)                   | 975                    |
| Rim Rec                    | DH44B/1.3 (multipiece) |
| ECE                        | E11-106R-006958        |

## Load capacity (Kg)

| km/h / bar                    | 0.8  | 1.0   | 1.4   | 1.6   | 2.0   | 2.4   | 2.8   | 3.2   | 3.4   | 3.8   |
|-------------------------------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 50                            | 6525 | 7395  | 9280  | 10295 | 11455 | 12325 | 13485 | 14500 | ---   | ---   |
| 40                            | 7115 | 8065  | 10120 | 11225 | 12490 | 13435 | 14700 | 15805 | ---   | ---   |
| 30                            | 7615 | 8630  | 10830 | 12010 | 13365 | 14380 | 15735 | 16915 | ---   | ---   |
| 10 LT                         | 9535 | 10805 | 13560 | 15040 | 16735 | 18005 | 19700 | 21180 | ---   | ---   |
| 10 HT                         | 7615 | 8630  | 10830 | 12010 | 13365 | 14380 | 15735 | 16915 | ---   | ---   |
| Upto 10 Cyc with front loader | ---  | 11960 | 15320 | 16795 | 19485 | 21365 | 23380 | 25395 | 25800 | 26870 |

\* For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 5/19/2024 12:52 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..