

## AGRIMAX TERIS - Tekniska specifikationer



### Description

Dagens kraftfulla skördemaskiner kräver däck som håller för tung utrustning och större laster, utan att skada grödan. BKT gör sitt yttersta för att förse dig med banbrytande radialdäck som förbättrar skörden. AGRIMAX TERIS är rätt val av partner för hela din verksamhet. Utmärkt dragförmåga och hög lastkapacitet är avgörande faktorer som ger den bästa prestandan vid alla skördarbeten. Det speciella skyddet i sidoväggen och förstärkt däckskuldra ökar motståndskraften – och förlänger produktens livslängd – även under krävande förhållanden och om det finns stubb på åkern.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Bomullsmaskin • Skördemaskin

Version	STANDARD
Type	TL
Tyre Size	900/60 R 32 CHO
LI/SS	185 A8/182 B

## Dimensions US Standard

Usa code	94040865
Section Width (inch)	34.4
Overall Diameter (inch)	75.2
Static Loaded Radius (inch)	34.4
Rolling Circumference (inch)	227.4
Rim Rec	DW 27 B
Rim Alt	DW 28 B ; DW 30 B
ECE	E4-106R-001433

## Load capacity (lbs)

mph / psi	12	15	20	23	29	35	41	46	52	58
30	7440	8430	10580	11740	13060	14050	15380	16530	17610	18740
25	8190	9280	11640	12920	14370	15460	16920	18190	19170	20390
20	8760	9930	12470	13820	15390	16560	18110	19470	20510	21820
10 Cyc	13510	15310	19210	21320	23720	25520	27920	30010	31630	33650
5 Cyc	14740	16700	20950	23250	25870	27830	30460	32740	34510	36700

Printed on 19/05/2024 15:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..