

EARTHMAX SR 25 PLUS - Ladda ned faktablad



Description

EARTHMAX SR 25 PLUS (G-2/L-2) är ett stålradialdäck särskilt avsett för väghyvlar och hjullastare som används under tuffa förhållanden vid vägbyggen och i gruvor. Det symmetriska slitbanemönstret har utmärkta självrensande egenskaper och ger utmärkt dragkraft och stabilitet vid terrängkörning.

UM

International Standard

Construction

 RADIAL

Machinery

Industri: Bulldozer • Väghyvlare • Hjullastare
OTR: Bulldozer • Väghyvlare • Hjullastare

| SIZE | Version | TRA Code | Star R | LI/SS | RIM REC | RIM ALT | OW | OD | SLR | RC | Type |
|------------|------------------------|----------|--------|---------------|---------|---------|-----|------|-----|------|------|
| 14.00 R 24 | CUT RESISTANT COMPOUND | G2/L2 | * | 153 A8/175 A2 | 8.00TG | 9.00GR | 359 | 1372 | 626 | 4146 | TL |

Printed on 5/18/2024 10:17 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..