

## EARTHMAX SR 35 - Tekniska specifikationer



### Description

Earthmax SR 35 är ett stålradialdäck med låg profil, avsett för midjestyrd dumprar och hjullastare. Earthmax SR 35 har både utmärkt dragkraft och stabilitet. Det kraftiga stålbelagda höljet är utomordentligt pålitligt och tåligt mot revor och punkteringar. Däcket finns tillgängligt med en skärtålig gummiblandning som ger en mycket lång livslängd även under svåra förhållanden.

### UM

International Standard

### Construction

RADIAL

### Machinery

OTR: Ramstyrd dumper (ADT) • Bulldozer • Hjullastare

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	775/65 R 29
LI/SS	195 B/206 A2

## Dimensions International Standard

TKPH	220
Overall Width (mm)	775
Overall Diameter (mm)	1752
Static Loaded Radius (mm)	787
Rolling Circumference (mm)	5311
Rim Rec	24.00/3.5
Rim Alt	24.00/3.0, 25.00/3.5
Star Rating	**/*
TRA Code	E3/L3

## Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75
50	10900	11200	11800	12150
10	15000	15500	16500	17000

Printed on 5/19/2024 4:18 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..