

EARTHMAX SR 41 - Tekniska specifikationer



Description

EARTHMAX SR 41 (E-4/L-4) är ett radialdäck helt i stål perfekt för ramstyrda dumprar, lastare och schaktmaskiner. Tack vare strukturen helt i stål och ett speciellt blockmönster ger EARTHMAX SR 41 utmärkt motståndskraft mot punkteringar och längre livslängd. EARTHMAX SR 41 är även tillgängligt i E4**** för dumpers med lågprofil (LPDT) som används i underjordisk drift.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Ramstyrd dumper (ADT) • Bulldozer • Hjullastare • Dumper med lågprofil

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	23.5 R 25
LI/SS	185 B/195 A2

Dimensions US Standard

Usa code	94053353
TMPH	110
Overall Width (inch)	24.2
Overall Diameter (inch)	63.4
Static Loaded Radius (inch)	28.5
Rolling Circumference (inch)	188.6
Rim Rec	19.50/2.5
Star Rating	**/*
TRA Code	E4/L4

Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	16500	17100	18200	18700	19800	20400
5	22700	23400	24700	25400	26800	-

Printed on 5/18/2024 5:27 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..