

EARTHMAX SR 468 - Ladda ned faktablad



Description

EARTHMAX SR 468 är ett stålradialdäck som utformats speciellt för anläggningsbilar. Det unika däcktönstret med speciella slitbanesammansättningar gör det perfekt för hårda, steniga och tuffa gruvförhållanden. De räfflade slitbaneblocken med rundspår och sammanflätade block säkerställer effektiv värmeavledning. Den robusta fyrkantiga axeln hjälper till att köra bort lösa stenar för att skydda däckets från skador. EARTHMAX SR 468 är framtaget med BKT:s toppmoderna teknik för att bära tunga laster, leverera längre livslängd och vara motståndskraftigt mot skärsår och punkteringar.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Stel dumper

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
37.00 R 57	CUT RESISTANT COMPOUND	E4	**	245 B	27.00/6.0	29.00/6.0	1030	3425	1520	10315	TL	725
37.00 R 57	HEAT RESISTANT COMPOUND	E4	**	245 B	27.00/6.0	29.00/6.0	1030	3425	1520	10315	TL	1020
37.00 R 57	STANDARD COMPOUND	E4	**	245 B	27.00/6.0	29.00/6.0	1030	3425	1520	10315	TL	850
40.00 R 57	CUT RESISTANT COMPOUND	E4	**	250 B	29.00/6.0	32.00/6.0	1125	3575	1595	10700	TL	800
40.00 R 57	HEAT RESISTANT COMPOUND	E4	**	250 B	29.00/6.0	32.00/6.0	1125	3575	1595	10700	TL	1130
40.00 R 57	STANDARD COMPOUND	E4	**	250 B	29.00/6.0	32.00/6.0	1125	3575	1595	10700	TL	950
46/90 R 57	CUT RESISTANT COMPOUND	E4	**	252 B	29.00/6.0	32.00/6.0	1140	3575	1590	10800	TL	825
46/90 R 57	HEAT RESISTANT COMPOUND	E4	**	252 B	29.00/6.0	32.00/6.0	1140	3575	1590	10800	TL	1165
46/90 R 57	STANDARD COMPOUND	E4	**	252 B	29.00/6.0	32.00/6.0	1140	3575	1590	10800	TL	980
50/80 R 57	CUT RESISTANT COMPOUND	E4	**	257 B	32.00/6.0	29.00/6.0	1205	3610	1597	10870	TL	950
50/80 R 57	HEAT RESISTANT COMPOUND	E4	**	257 B	32.00/6.0	29.00/6.0	1205	3610	1597	10870	TL	1340
50/80 R 57	STANDARD COMPOUND	E4	**	257 B	32.00/6.0	29.00/6.0	1205	3610	1597	10870	TL	1130

Printed on 5/19/2024 5:07 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..