

## EARTHMAX SR 468 - Ladda ned faktablad



### Description

EARTHMAX SR 468 är ett stålradialdäck som utformats speciellt för anläggningsbilar. Det unika däcktönstret med speciella slitbanesammansättningar gör det perfekt för hårda, steniga och tuffa gruvförhållanden. De räfflade slitbaneblocken med rundspår och sammanflätade block säkerställer effektiv värmeavledning. Den robusta fyrkantiga axeln hjälper till att köra bort lösa stenar för att skydda däckets från skador. EARTHMAX SR 468 är framtaget med BKT:s toppmoderna teknik för att bära tunga laster, leverera längre livslängd och vara motståndskraftigt mot skärsår och punkteringar.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Stel dumper

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
37.00 R 57	CUT RESISTANT COMPOUND	94069354	E4	**	245 B	27.00/6.0	29.00/6.0	40.6	134.8	59.8	406.1	TL	497
37.00 R 57	HEAT RESISTANT COMPOUND	94069347	E4	**	245 B	27.00/6.0	29.00/6.0	40.6	134.8	59.8	406.1	TL	699
37.00 R 57	STANDARD COMPOUND	94069361	E4	**	245 B	27.00/6.0	29.00/6.0	40.6	134.8	59.8	406.1	TL	582
40.00 R 57	CUT RESISTANT COMPOUND	94068845	E4	**	250 B	29.00/6.0	32.00/6.0	44.3	140.7	62.8	421.3	TL	548
40.00 R 57	HEAT RESISTANT COMPOUND	94067381	E4	**	250 B	29.00/6.0	32.00/6.0	44.3	140.7	62.8	421.3	TL	774
40.00 R 57	STANDARD COMPOUND	94068852	E4	**	250 B	29.00/6.0	32.00/6.0	44.3	140.7	62.8	421.3	TL	651
46/90 R 57	CUT RESISTANT COMPOUND	94070589	E4	**	252 B	29.00/6.0	32.00/6.0	44.9	140.7	62.6	425.2	TL	565
46/90 R 57	HEAT RESISTANT COMPOUND	94070596	E4	**	252 B	29.00/6.0	32.00/6.0	44.9	140.7	62.6	425.2	TL	798
46/90 R 57	STANDARD COMPOUND	94070602	E4	**	252 B	29.00/6.0	32.00/6.0	44.9	140.7	62.6	425.2	TL	671
50/80 R 57	CUT RESISTANT COMPOUND	94075164	E4	**	257 B	32.00/6.0	29.00/6.0	47.4	142.1	62.9	428	TL	651
50/80 R 57	HEAT RESISTANT COMPOUND	94075157	E4	**	257 B	32.00/6.0	29.00/6.0	47.4	142.1	62.9	428	TL	918
50/80 R 57	STANDARD COMPOUND	94074228	E4	**	257 B	32.00/6.0	29.00/6.0	47.4	142.1	62.9	428	TL	774

Printed on 5/19/2024 6:59 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..