

EARTHMAX SR 484 - Ladda ned faktablad



Description

EARTHMAX SR 484 är ett stålradialdäck som är särskilt utformat för stela dumprar för transport i dagbrott. Det har ett unikt E-3-däckmönster med speciell gummisammansättning som säkerställer utmärkt skydd i stränga förhållanden, tillsammans med förbättrad dragkraft och utmärkta självrengörande egenskaper. Dess konstruktion helt i stål med stålbälten i flera lager möjliggör överlägset skydd mot stötar och penetrering av stenar, för att öka drifttiden och därmed produktiviteten. EARTHMAX SR 484 har en fyrkantig axeldesign som maximerar markkontakten för utmärkt manövrerbarhet och stabilitet. Detta BKT-däck är särskilt utformat för högre fart och långa distanser.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Stel dumper

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
27.00 R 49	CUT RESISTANT COMPOUND	E3	**	223 B	19.50/4.0	--	735	2647	1193	8055	TL	525
27.00 R 49	HEAT RESISTANT COMPOUND	E3	**	223 B	19.50/4.0	--	735	2647	1193	8055	TL	710
27.00 R 49	STANDARD COMPOUND	E3	**	223 B	19.50/4.0	--	735	2647	1193	8055	TL	610

Printed on 5/19/2024 5:35 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..