

EARTHMAX SR 55 - Tekniska specifikationer



Description

EARTHMAX SR 55 M är ett radialdäck helt i stål som är specialdesignat för hjullastare, bandschaktare och dumpers med lågprofil som körs i de mest krävande stenbrotts- och gruvdriftsmiljöerna samt på skrotupplag. Tack vare det utmärkta skyddet mot revor som uppnås med ett extra djupt och slätt mönster kan EARTHMAX SR 55 erbjuda förstklassig produktivitet med minskade driftstopp kombinerat med utmärkt hållbarhet. Maskinoperatörer lär också uppskatta den extraordinära stabiliteten och dragförmågan.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Bulldozer • Gruvlastmaskin • Hjullastare

Version	CUT RESISTANT COMPOUND
Type	TT
Tyre Size	12.00 R 24
LI/SS	175 A2

Dimensions International Standard

Overall Width (mm)	305
Overall Diameter (mm)	1274
Static Loaded Radius (mm)	572
Rolling Circumference (mm)	3787
Rim Rec	8.50/1.3
Rim Alt	8.0,9.0
Star Rating	**
TRA Code	L5S

Load capacity (Kg)

km/h / bar	8.25
10	6900

Printed on 5/19/2024 5:38 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..