

FL 695 - Tekniska specifikationer



Description

FL 695 har designats specifikt för släpvagnar i byggindustrin och transporttillämpningar inom jordbruksindustrin med ett unikt slitbanemönster i mittblocket. Tack vare sitt starka däckhölje kan FL 695 bära tunga laster och samtidigt bibehålla stabilitet under alla förhållanden. Dess djupa mönster säkerställer optimal självrensning både på vägar och i terrängen. Flera lager med kordkablar i stål förstärker detta mönster mot punkteringar.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Släpvagn

Industri: Släpvagn

Version	STEEL BELTED
Type	TL
Tyre Size	710/50 R 30.5
LI/SS	177 D
LI/SS DRIVE WHEEL	177 D
LI/SS FREE ROLLING	177 D

Dimensions US Standard

Usa code	94074082
Section Width (inch)	27.6
Overall Diameter (inch)	58.7
Static Loaded Radius (inch)	27.2
Rolling Circumference (inch)	179.3
Rim Rec	AG24.00
Rim Alt	AG20.00
ECE	E11-106R-008661

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	65	73
40	--	--	--	8210	9500	10790	11920	13040	14330	15290	16090
30	--	--	--	9940	11500	13050	14420	15780	17340	18510	19480
25	--	8100	9850	11170	12920	14670	16200	17740	19490	20800	21890
20	7050	8990	10950	12400	14340	16290	17990	19700	21640	23090	24300
15	7390	9410	11450	12970	15010	17040	18830	20600	22640	24160	25430
10	7700	9830	11960	13550	15670	17800	19650	21520	23640	25230	26550
5	8410	10720	13040	14780	17100	19410	21440	23470	25780	27520	28970

Printed on 5/18/2024 10:43 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..