

RIDEMAX FL 693 M - Tekniska specifikationer



Description

RIDEMAX FL 693 M är det idealiska radialdäcket för användare som regelbundet kör på väg med släpvagn/tankbil. RIDEMAX FL 693 M är i själva verket designat för 75 procent användning på väg och erbjuder utmärkt vägprestanda genom att prioritera både komfort och självrensande egenskaper. Hastighetsindexklasserna D/E i serien imponerar med högre hastigheter vid körning på väg, vilket leder till betydande tidsbesparingar. Det låga rullningsmotståndet bidrar till lägre bränsleförbrukning, samtidigt som den förstärkta vulsten och stålbalten säkerställer extra hållbarhet.

UM

International Standard

Construction

 RADIAL

Machinery

Lantbruk: Tankbil • Släpvagn

| | |
|-----------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 650/50 R 22.5 |
| LI/SS | 168 D |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Section Width (mm) | 645 |
| Overall Diameter (mm) | 1222 |
| Static Loaded Radius (mm) | 535 |
| Rolling Circumference (mm) | 3715 |
| SRI (mm) | 575 |
| Rim Rec | AG 20.00 |
| ECE | E11-106R-006489 |

Load capacity (Kg)

| km/h / bar | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 5.0 |
|------------|------|------|------|------|------|------|------|------|------|-------|
| 70 | 1480 | 1890 | 2295 | 2605 | 3010 | 3420 | 3775 | 4135 | 4540 | 5100 |
| 65 | 1625 | 2075 | 2520 | 2860 | 3305 | 3755 | 4145 | 4540 | 4985 | 5600 |
| 50 | 1970 | 2510 | 3080 | 3460 | 4005 | 4545 | 5020 | 5495 | 6035 | 6780 |
| 40 | 2210 | 2820 | 3465 | 3890 | 4500 | 5110 | 5640 | 6175 | 6785 | 7620 |
| 30 | 2455 | 3135 | 3845 | 4315 | 4995 | 5670 | 6265 | 6855 | 7530 | 8460 |
| 25 | 2570 | 3275 | 4020 | 4515 | 5225 | 5930 | 6550 | 7170 | 7880 | 8850 |
| 10 | 2925 | 3730 | 4580 | 5145 | 5950 | 6755 | 7460 | 8165 | 8975 | 10080 |

Printed on 5/19/2024 12:41 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..