

FL 695 - Teknik Özellikler



Description

FL 695, benzersiz merkezi blok sırt deseni ile inşaat ve tarım taşıma uygulamalarında kullanılan römorklar için özel olarak tasarlanmıştır. Güçlü gövdesi sayesinde FL 695 tüm koşullarda sabitliği koruyarak ağır yükler taşıyabilir ve derin sırtı yolda ve yol dışında uygulamalar esnasında optimum kendi kendini temizleme sağlar. Çoklu çelik kord katmanları, bu deseni delinmelere karşı güçlü kılar.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Römork

Endüstriyel: Römork

Version	STEEL BELTED
Type	TL
Tyre Size	650/55 R 26.5
LI/SS	178 D

Dimensions US Standard

Usa code	94067886
Section Width (inch)	24.8
Overall Diameter (inch)	54.7
Static Loaded Radius (inch)	24.8
Rolling Circumference (inch)	167
Rim Rec	AG20.00
Rim Alt	AG22.00
ECE	E11-106R-007052

Load capacity (lbs)

mph / psi	012	17	23	29	35	41	46	52	58	65	73	80	87
40	--	--	--	7440	8600	9750	10750	11740	12900	13720	14550	15540	16530
30	--	--	--	9010	10410	11810	13010	14210	15610	16610	17610	18820	20010
25	--	7430	9230	10120	11690	13270	14620	15970	17550	18670	19800	21140	22490
20	6250	8240	10240	11240	12980	14740	16240	17740	19480	20720	21980	23480	24970
15	6540	8630	10710	11760	13590	15420	16990	18550	20380	21690	22990	24560	26120
10	6820	9010	11190	12280	14190	16100	17740	19380	21280	22650	24010	25650	27280
5	7440	9820	12200	13390	15480	17560	19340	21130	23210	24700	26190	27980	29760

Printed on 5/19/2024 4:16 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..