

## MULTIMAX MP 527 - Teknik Özellikler



### Description

MULTIMAX MP 527 tarımsal sanayi uygulamalarında teleskopik yükleyiciler ve küçük yükleyiciler için tasarlanmış çok amaçlı bir radyal lastiktir. Lastik, daha sert yüzeylerde bile mükemmel çekiş sağlayan bir blok diş deseni tasarımına sahiptir. Güçlü yanak, kaldırma modunda olağanüstü sabitleme sağlar. MULTIMAX MP 527, kesilme ve kopmaya karşı dirençli özel bir hamura ve uzun bir kullanım ömrüne sahiptir.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Zirai: Küçük yükleyici • Teleskopik yükleyici  
Endüstriyel: Küçük yükleyici • Teleskopik yükleyici

Version	STANDARD
Type	TL
Tyre Size	500/70 R 24 IND
LI/SS	164 A8/B

## Dimensions International Standard

Section Width (mm)	503
Overall Diameter (mm)	1310
Static Loaded Radius (mm)	597
Rolling Circumference (mm)	4019
SRI (mm)	625
Rim Rec	DW 16 L
Rim Alt	DW 15 L ; DW 18 L
ECE	E4-106R-002658

## Load capacity (Kg)

km/h / bar	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	2400	2850	3250	3700	4150	4450	5000	-	-
40	2400	2850	3250	3700	4150	4450	5000	-	-
30	2570	3050	3480	3960	4445	4765	5350	-	-
25	2665	3165	3610	4110	4610	4940	5550	-	-
10 Cyc.	2925	3600	4240	4875	5550	6040	6825	7200	7500
Static	4485	5520	6500	7475	8510	9260	10465	11040	11500

Printed on 5/19/2024 5:09 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..