

RIDEMAX FL 693 M - Teknik Özellikler



Description

RIDEMAX FL 693 M, sıklıkla römork/tanker kamyonlarla yolda seyahat edenler için ideal bir radyal lastiktir. %75 yolda kullanım için tasarlanan RIDEMAX FL 693 M, hem konfor hem de kendi kendini temizleme özelliklerine öncelik vererek mükemmel yol performansı sağlar. Serinin D/E hız endeksi sınıfları, yolda seyahat ederken daha yüksek hızları temsil eder ve bu da önemli ölçüde zaman tasarrufu sağlar. Düşük yuvarlanma direnci daha az yakıt tüketimine katkıda bulunurken, güçlendirilmiş bir damak ve çelik kuşaklar daha fazla dayanıklılık sağlar.

UM

International Standard

Construction

 RADIAL

Machinery

Zirai: Tanker • Römork

Version	STANDARD
Type	TL
Tyre Size	710/50 R 30.5
LI/SS	173 D

Dimensions International Standard

Section Width (mm)	727
Overall Diameter (mm)	1485
Static Loaded Radius (mm)	676
Rolling Circumference (mm)	4533
SRI (mm)	700
Rim Rec	AG 24.00
Rim Alt	AG 20.00
ECE	E4-106R-001498

Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	2220	2520	3060	3540	4080	4620	4980	5520	6000
65	2405	2730	3315	3835	4420	5005	5395	5980	6500
50	2915	3305	4015	4645	5350	6060	6530	7240	7865
40	3275	3715	4510	5220	6015	6810	7340	8135	8840
25	3805	4315	5240	6060	6985	7910	8525	9450	10270
10	4330	4915	5970	6905	7960	9010	9715	10765	11700

Printed on 5/19/2024 2:54 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..