

## RIDEMAX FL 693 M - Teknik Özellikler



### Description

RIDEMAX FL 693 M, sıklıkla römork/tanker kamyonlarla yolda seyahat edenler için ideal bir radyal lastiktir. %75 yolda kullanım için tasarlanan RIDEMAX FL 693 M, hem konfor hem de kendi kendini temizleme özelliklerine öncelik vererek mükemmel yol performansı sağlar. Serinin D/E hız endeksi sınıfları, yolda seyahat ederken daha yüksek hızları temsil eder ve bu da önemli ölçüde zaman tasarrufu sağlar. Düşük yuvarlanma direnci daha az yakıt tüketimine katkıda bulunurken, güçlendirilmiş bir damak ve çelik kuşaklar daha fazla dayanıklılık sağlar.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Zirai: Tanker • Römork

Version	STANDARD
Type	TL
Tyre Size	850/50 R 30.5
LI/SS	182 D

## Dimensions US Standard

Usa code	94034505
Section Width (inch)	33.9
Overall Diameter (inch)	64
Static Loaded Radius (inch)	28.3
Rolling Circumference (inch)	193.9
Rim Rec	AG 28.00
ECE	E4-106R-001500

## Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	6320	7160	8700	10060	11600	13140	14160	15700	17050
40	6930	7870	9560	11060	12740	14430	15550	17240	18740
30	8400	9520	11570	13380	15420	17460	18830	20870	22670
25	9440	10710	13010	15050	17340	19630	21150	23460	25480
15	10970	12440	15100	17470	20140	22810	24580	27250	29610
5	12490	14170	17210	19910	22940	25980	28000	31040	33730

Printed on 5/19/2024 5:22 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..