

## RIDEMAX IT 697 (M+S) - Teknik Özellikler



### Description

RIDEMAX IT 697 M+S kışın yapılan çalışmalar sırasında modern çiftçilik yüklenicilerinin ihtiyaçlarını karşılamak için en iyi yanıttır. Nakliye ve belediye uygulamaları için mükemmeldir. Traktörlerde kullanılan bu kış lastiği, kar zincirleri takmaya gerek kalmadan buzlu ve karlı yollardaki tüm çalışmalarda sıra dışı bir yol tutuş sağlar. Sırt kanalları ve güçlü gövdesi sayesinde, traktör yüksek hızlarda da tam sabitleme ile sürülebilir. Sırt tasarımı, ağır hizmetler için özel olarak geliştirilmiştir ve yakıt ekonomisiyle birlikte mükemmel sabitleme sağlayan düşük yuvarlanma direnci sunar.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Zirai: Traktör

|           |                 |
|-----------|-----------------|
| Version   | STANDARD        |
| Type      | TL              |
| Tyre Size | 600/65 R 38 IND |
| LI/SS     | 166 D/170 A8    |

## Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94062812        |
| Section Width (inch)         | 23.2            |
| Overall Diameter (inch)      | 68.7            |
| Static Loaded Radius (inch)  | 31.3            |
| Rolling Circumference (inch) | 209.3           |
| Rim Rec                      | DW 18 L         |
| Rim Alt                      | DW 20 B         |
| ECE                          | E11-106R-005855 |

## Load capacity (lbs)

| mph / psi | 17   | 23   | 29   | 35    | 41    | 46    |
|-----------|------|------|------|-------|-------|-------|
| 40        | 5490 | 6780 | 7950 | 9230  | 10390 | 11680 |
| 30        | 5930 | 7320 | 8590 | 9980  | 11230 | 12620 |
| 25        | 6220 | 7670 | 8990 | 10450 | 11770 | 13230 |
| 20        | 6590 | 8130 | 9530 | 11080 | 12480 | 14020 |

Printed on 5/18/2024 8:44 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..