

AGRIMAX TERIS - Technical Specifications



Description

Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations. Excellent traction properties and high load capacity are its essential features providing best performance in all harvesting operations. The special sidewall protection and a reinforced shoulder increase resistance - thus extending the product life-cycle – also in harsh conditions and if there are stubbles in the fields.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Cotton Picker • Harvester

Version	STANDARD
Type	TL
Tyre Size	900/60 R 32 CHO
LI/SS	181 A8/178 B

Dimensions US Standard

Usa code	94029723
Section Width (inch)	34.9
Overall Diameter (inch)	75.2
Static Loaded Radius (inch)	33.6
Rolling Circumference (inch)	224.4
Rim Rec	DW 27 B
Rim Alt	DW 28 B ; DW 30 B
ECE	E4-106R-001431

Load capacity (lbs)

mph / psi	12	15	20	23	29	35	41	46
30	7440	8430	10580	11740	13060	14050	15380	16530
25	8190	9280	11640	12920	14370	15460	16920	18190
20	8760	9930	12470	13820	15390	16560	18110	19470
10 Cyc	13510	15310	19210	21320	23720	25520	27920	30010
5 Cyc	14740	16700	20950	23250	25870	27830	30460	32740

Printed on 5/19/2024 5:02 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..