



# AGRIMAX TERIS - Data Sheet



## Description

Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations. Excellent traction properties and high load capacity are its essential features providing best performance in all harvesting operations. The special sidewall protection and a reinforced shoulder increase resistance - thus extending the product life-cycle - also in harsh conditions and if there are stubbles in the fields.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Agriculture: Cotton Picker • Harvester

| SIZE                               | Version  | LI/SS           | RIM REC              | RIM ALT   | SW   | OD   | SLR | RC   | SRI | Type | ECE             |
|------------------------------------|----------|-----------------|----------------------|---|------|------|-----|------|-----|------|-----------------|
| 620/75 R 26<br>CHO                 | STANDARD | 166 A8/B        | DW 20 B              |   | 625  | 1590 | 730 | 4851 | 750 | TL   | E4-106R-001419  |
| 750/65 R 26<br>CHO<br>(28L R 26)   | STANDARD | 166 A8/B        | DW 25 B              | DW 23 B   | 764  | 1636 | 713 | 4908 | 750 | TL   | E4-106R-000810  |
| 750/65 R 26<br>CHO<br>(28L R 26)   | STANDARD | 171 A8/B        | DW 25 B              | DW 23 B   | 764  | 1636 | 713 | 4908 | 750 | TL   | E4-106R-001496  |
| 710/55 R 28<br>CHO                 | STANDARD | 164 A8/B        | DW 23 B              |   | 716  | 1493 | 663 | 4442 | 700 | TL   | E11-106R-005940 |
| 620/75 R 30<br>CHO                 | STANDARD | 168 A8/B        | DW 20 B              |   | 625  | 1692 | 779 | 5169 | 800 | TL   | E4-106R-001420  |
| 1050/50 R 32<br>CHO                | STANDARD | 184<br>A8/181 B | 36.0 VA              |   | 1059 | 1893 | 840 | 5685 | 875 | TL   | E4-106R-000813  |
| 650/75 R 32<br>CHO                 | STANDARD | 172 A8/B        | DW 21 B              | DW 20 B ; DW 23 B                                     | 670  | 1795 | 816 | 5378 | 850 | TL   | E4-106R-001425  |
| 800/65 R 32<br>CHO<br>(30.5L R 32) | STANDARD | 178<br>A8/175 B | DW 27 B              | DW 25 B ; DH 27 B                                     | 818  | 1853 | 838 | 5551 | 875 | TL   | E4-106R-001430  |
| 900/60 R 32<br>CHO                 | STANDARD | 185<br>A8/182 B | DW 27 B              | DW 28 B ; DW 30 B                                     | 875  | 1910 | 875 | 5775 | 900 | TL   | E4-106R-001433  |
| 900/60 R 32<br>CHO                 | STANDARD | 181<br>A8/178 B | DW 27 B              | DW 28 B ; DW 30 B                                     | 886  | 1910 | 854 | 5700 | 900 | TL   | E4-106R-001431  |
| IF 710/75 R 32<br>CFO              | STANDARD | 183 A8/B        | DW 25 B              | DW 23 B   | 716  | 1879 | 851 | 5653 | 875 | TL   | E11-106R-005025 |
| IF 580/80 R 34<br>CFO              | STANDARD | 177 D           | DW 20 B ; DW<br>20 A | DW 21 A ; DW 21 B                                     | 586  | 1792 | 810 | 5422 | 850 | TL   | E4-106R-001833  |
| IF 710/75 R 34<br>CFO              | STANDARD | 184 A8/B        | DW 25 B              |   | 716  | 1930 | 870 | 5852 | 900 | TL   | E11-106R-004899 |
| 520/85 R 42                        | STANDARD | 168 D           | DW 16 L              | W15L ; DW15L ; DD16L ; W16L ; DD18L ;<br>DW18L ; W18L | 516  | 1951 | 890 | 5851 | 925 | TL   | E4-106R-001829  |

Printed on 5/19/2024 12:24 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..