

MULTIMAX MP 522 - Technical Specifications



Description

MULTIMAX MP 522 is the BKT multi-purpose tire developed for agro-industrial applications. It is suitable for all lifting and loading operations on vehicles such as telehandlers and compact loaders. Stability and traction are its strengths as well as outstanding puncture resistance. Thanks to its special compound, MULTIMAX MP 522 has an incredible cut and chip resistance.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Compact Loader • Telehandler

Industrial: Compact Loader • Telehandler

Version	STANDARD
Type	TL
Tyre Size	280/80 R 18 IND (10.5/80 R 18)
LI/SS	132 A8/B

Dimensions International Standard

Section Width (mm)	282
Overall Diameter (mm)	907
Static Loaded Radius (mm)	421
Rolling Circumference (mm)	2748
SRI (mm)	425
Rim Rec	W 9 ; 9 ; 9 SDC
Rim Alt	W 8 ; W 10
ECE	E11-106R-002962

Load capacity (Kg)

km/h / bar	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	960	1140	1300	1480	1660	1780	2000	-	-
40	960	1140	1300	1480	1660	1780	2000	-	-
30	1030	1220	1395	1585	1780	1905	2140	-	-
25	1070	1270	1445	1645	1845	1980	2220	-	-
10 Cyc.	1170	1440	1695	1950	2220	2415	2730	2880	3000
Static	1795	2210	2600	2990	3405	3705	4190	4420	4600

Printed on 5/19/2024 12:00 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..