

MULTIMAX MP 527 - Data Sheet



Description

MULTIMAX MP 527 is a multi-purpose radial tire designed for telehandlers and compact loaders in agro-industrial applications. The tire shows a block pattern design providing excellent traction even on the harder surfaces. The strong sidewall ensures outstanding stability in lift mode. MULTIMAX MP 527 is made of a special cut-and-chip-resistant compound providing and a long service life.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Compact Loader • Telehandler

Industrial: Compact Loader • Telehandler

| SIZE | Version | LI/SS | RIM REC | RIM ALT | SW | OD | SLR | RC | SRI | Type | ECE |
|---------------------------------------|----------|----------|------------------|--|-----|------|-----|------|-----|------|-----------------|
| 340/80 R 18 IND | STANDARD | 143 A8/B | 11; 11 SDC; W 11 | W 10; 12; 12 SDC | 343 | 1001 | 455 | 3028 | 475 | TL | E4-106R-002981 |
| 360/70 R 18 IND | STANDARD | 142 A8/B | 11 | W10; 11 SDC; W11; 12; 12 SDC | 360 | 969 | 439 | 2887 | 475 | TL | E11-106R-002996 |
| 340/80 R 20 IND | STANDARD | 144 A8/B | 11 | W10; 11 SDC; W11; 12; 12 SDC | 343 | 1052 | 483 | 3176 | 500 | TL | E11-106R-003957 |
| 400/70 R 20 IND (16.0/70 R 20) | STANDARD | 149 A8/B | 13 | 12 SDC; 13 SDC; 14 | 404 | 1068 | 494 | 3282 | 525 | TL | E4-106R-002656 |
| 400/70 R 24 IND | STANDARD | 152 A8/B | 13 | DW 12; DW 13; DW 13 L; 13 SDC; DW 14 L | 404 | 1170 | 542 | 3597 | 575 | TL | E11-106R-003958 |
| 400/80 R 24 IND | STANDARD | 162 A8/B | DW 13 | DW 12; DW 13 L; DW 14 L | 404 | 1250 | 578 | 3834 | 600 | TL | E11-106R-002982 |
| 440/80 R 24 IND | STANDARD | 161 A8/B | DW 14 L | DW 13; DW 13 L; DW 15 L | 441 | 1314 | 601 | 3985 | 625 | TL | E4-106R-002657 |
| 460/70 R 24 IND (17.5L R 24) | STANDARD | 159 A8/B | DW 15 L | DW 14 L; DW 16 L | 465 | 1254 | 574 | 3801 | 600 | TL | E11-106R-002983 |
| 500/70 R 24 IND | STANDARD | 164 A8/B | DW 16 L | DW 15 L; DW 18 L | 503 | 1310 | 597 | 4019 | 625 | TL | E4-106R-002658 |
| 480/80 R 26 IND | STANDARD | 160 A8/B | DW 15 L | DW 16 L | 479 | 1428 | 642 | 4259 | 675 | TL | E11-106R-004069 |
| 440/80 R 28 IND | STANDARD | 156 A8/B | DW 14 L | DW 13; DW 13 L; DW 15 L | 441 | 1415 | 648 | 4270 | 675 | TL | E11-106R-002984 |

Printed on 5/19/2024 1:40 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..