

## RIDEMAX FL 693 M - Technical Specifications



### Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	600/55 R 26.5
LI/SS	165 D

## Dimensions US Standard

Usa code	94047277
Section Width (inch)	24.1
Overall Diameter (inch)	52.5
Static Loaded Radius (inch)	23.1
Rolling Circumference (inch)	159.5
Rim Rec	AG 20.00
ECE	E4-106R-002398

## Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	3840	4340	5280	6110	7030	7970	8590	9510	10340
40	4210	4770	5800	6700	7730	8750	9420	10450	11350
30	5090	5780	7010	8110	9350	10590	11420	12650	13750
25	5720	6490	7880	9120	10500	11890	12820	14210	15440
15	6650	7540	9160	10590	12210	13820	14900	16510	17940
5	7570	8590	10430	12060	13900	15740	16960	18800	20440

Printed on 5/19/2024 5:32 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..