

RIDEMAX FL 693 M - Technical Specifications



Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	650/50 R 22.5
LI/SS	168 D

Dimensions US Standard

Usa code	94055654
Section Width (inch)	25.4
Overall Diameter (inch)	48.1
Static Loaded Radius (inch)	21.1
Rolling Circumference (inch)	146.3
Rim Rec	AG 20.00
ECE	E11-106R-006489

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	73
45	3260	4170	5060	5740	6640	7540	8320	9120	10010	11240
40	3580	4570	5560	6300	7290	8280	9140	10010	10990	12300
30	4340	5530	6790	7630	8830	10020	11070	12110	13300	14950
25	4870	6220	7640	8580	9920	11260	12430	13610	14960	16800
20	5410	6910	8480	9510	11010	12500	13810	15110	16600	18650
15	5670	7220	8860	9950	11520	13070	14440	15810	17370	19510
5	6450	8220	10100	11340	13120	14890	16450	18000	19790	22220

Printed on 5/19/2024 6:13 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..