

AGRIMAX RT 600 - Technical Specifications

Description

AGRIMAX RT 600 is the ideal tire for grassland, harvesting and spreading applications. Thanks to its large contact area, AGRIMAX RT 600 ensures an excellent pressure distribution on the land reducing damage on grassland and protecting your soil. Thanks to its round shoulder technology, the reinforced bead and increased number of lugs, it guarantees great stability and traction.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Harvester • Spreader • Tractor



Version	STANDARD
Type	TL
Tyre Size	1050/50 R32
LI/SS	184 A8/181 B

Dimensions US Standard

Usa code	94040728
Section Width (inch)	41.7
Overall Diameter (inch)	73.3
Static Loaded Radius (inch)	32.5
Rolling Circumference (inch)	224.4
Rim Rec	36.0 VA
ECE	E4-106R-000813

Load capacity (lbs)

mph / psi	12	15	20	23	29	35	41	46	49	55
30	8190	9280	11640	12920	14370	15460	16920	18190	-	-
25	8930	10120	12700	14090	15670	16860	18450	19840	-	-
20	9560	10840	13590	15080	16780	18050	19750	21230	-	-
5 LT	11970	13570	17020	18880	21010	22610	24730	26590	-	-
5 HT	9560	10840	13590	15080	16780	18050	19750	21230	-	-
5 Cyc	-	15010	19230	21090	24460	25470	27880	29970	31290	33730

Printed on 5/5/2024 7:16 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..