

AGRIMAX TERIS - Technical Specifications



Description

Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations. Excellent traction properties and high load capacity are its essential features providing best performance in all harvesting operations. The special sidewall protection and a reinforced shoulder increase resistance - thus extending the product life-cycle – also in harsh conditions and if there are stubbles in the fields.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Cotton Picker • Harvester

Version	STANDARD
Type	TL
Tyre Size	IF 710/75 R 34 CFO
LI/SS	184 A8/B

Dimensions US Standard

Usa code	94058723
Section Width (inch)	28.2
Overall Diameter (inch)	76
Static Loaded Radius (inch)	34.3
Rolling Circumference (inch)	230.4
Rim Rec	DW 25 B
ECE	E11-106R-004899

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	46
30	7740	8930	10120	11510	12700	14090	15670	16860	18450	19840
25	7740	8930	10120	11510	12700	14090	15670	16860	18450	19840
20	8290	9560	10840	12320	13590	15080	16780	18050	19750	21230
10 Cyc*	12780	14740	16700	18990	20950	23250	25870	27830	30460	32740
5 Cyc*	13930	16070	18220	20720	22860	25360	28220	30360	33220	35710

* - * For 15 & 10 Cyc application inflation pressure to be increased by 0.8 bar.

Printed on 5/18/2024 4:18 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..