

AGRIMAX TURF RT 333 - Technical Specifications



Description

AGRIMAX TURF RT 333 (R-3+) is a radial tire designed for small tractors in gardening, vineyards and orchards applications. Its rounded shoulder design provides low soil compaction and makes it extremely delicate on the ground. Its unique extra-deep tread (R-3+) and the special design with directional blocks stand for excellent traction both in the field and on the road, and an extended tire life cycle. AGRIMAX TURF RT 333 (R-3+) ensures great self-cleaning properties and thanks to its low rolling resistance, allows for significant fuel saving.

UM

US Standard

Construction



RADIAL

Machinery

Agriculture: Orchard Harvester • Small Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	200/70 R 16
LI/SS	94 A8/B

Dimensions US Standard

Usa code	94074136
Section Width (inch)	7.9
Overall Diameter (inch)	27
Static Loaded Radius (inch)	12.5
Rolling Circumference (inch)	80.9
Rim Rec	W 6
ECE	E11-106R-008659
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
30	690	800	930	1040	1160	1280	1380	1480
25	690	800	930	1040	1160	1280	1380	1480
20	750	860	990	1110	1250	1370	1480	1590
5 LT	940	1080	1230	1390	1550	1710	1850	1980
5 HT	750	860	990	1110	1250	1370	1480	1590

Printed on 5/18/2024 12:48 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..