

AGRIMAX TURF RT 333 - Technical Specifications



Description

AGRIMAX TURF RT 333 (R-3+) is a radial tire designed for small tractors in gardening, vineyards and orchards applications. Its rounded shoulder design provides low soil compaction and makes it extremely delicate on the ground. Its unique extra-deep tread (R-3+) and the special design with directional blocks stand for excellent traction both in the field and on the road, and an extended tire life cycle. AGRIMAX TURF RT 333 (R-3+) ensures great self-cleaning properties and thanks to its low rolling resistance, allows for significant fuel saving.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Orchard Harvester • Small Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	380/70 R 24
LI/SS	125 A8/125 B

Dimensions US Standard

Usa code	94068838
Section Width (inch)	15
Overall Diameter (inch)	46.9
Static Loaded Radius (inch)	21
Rolling Circumference (inch)	139.3
Rim Rec	W 12
Rim Alt	W 11 ; W 13
ECE	E11-106R-007112

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	2010	2340	2660	2990	3320	3640
25	2010	2340	2660	2990	3320	3640
20	2150	2510	2860	3210	3570	3910
5 LT	2690	3140	3580	4020	4460	4890
5 HT	2150	2510	2860	3210	3570	3910

Printed on 5/5/2024 5:22 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..