

AGRIMAX V-FLECTO - Technical Specifications



Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the exclusive VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 650/60 R 34
LI/SS	168 D

Dimensions US Standard

Usa code	94001222
Section Width (inch)	26
Overall Diameter (inch)	66
Static Loaded Radius (inch)	29.5
Rolling Circumference (inch)	196.7
Rim Rec	DW 23 B
Rim Alt	DW21B
ECE	E11-106R-007210

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29
45	5740	6640	7540	8550	9340	10120	11240
From 40 to 25	6300	7290	8280	9390	10250	11110	12350
20	6430	7440	8440	9580	10460	11340	12600
12	6560	7580	8610	9770	10660	11560	12840
5	6930	8010	9100	10330	11280	12220	13580
*Upto 5 Cyc with front loader	8820	10210	11580	13140	14350	15560	17280
5 HT	6430	7440	8440	9580	10460	11340	12600

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 5/5/2024 6:17 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..