

AGRIMAX V-FLECTO - Technical Specifications



Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the exclusive VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 710/60 R 42 NRO
LI/SS	173 D

Dimensions US Standard

Usa code	94053377
Section Width (inch)	28
Overall Diameter (inch)	76
Static Loaded Radius (inch)	33.9
Rolling Circumference (inch)	227.8
Rim Rec	DW 25 B
Rim Alt	DW 23 B ; MW 25 B
Narrow Rim option	DW 23 B
ECE	E11-106R-002998
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
45	7160	8340	9510	10690	11860	13040
from 40 to 25	7880	9170	10460	11750	13040	14330
20	8040	9350	10660	11980	13290	14620
12	8190	9530	10870	12210	13560	14900
5	8660	10090	11500	12920	14340	15760
*Upto 5 Cyc with front loader	11030	12830	14640	16450	18250	20060
5 HT	8040	9350	10660	11980	13290	14620

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 5/18/2024 12:48 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..