

AGRIMAX V-FLECTO - Technical Specifications



Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the exclusive VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 710/75 R 42
LI/SS	184 D

Dimensions US Standard

Usa code	94075447
Section Width (inch)	28.7
Overall Diameter (inch)	84.6
Static Loaded Radius (inch)	36.9
Rolling Circumference (inch)	252.4
Rim Rec	DW 24 B
Rim Alt	DW 23 B ; DW 25 B
ECE	E11-106R-009074
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29
45	9030	10470	11920	13540	14980	16420	18050
From 40 to 25	9920	11510	13090	14880	16470	18050	19840
20	10120	11730	13350	15180	16790	18410	20240
12	10320	11960	13610	15480	17120	18770	20630
5	10910	12650	14400	16370	18110	19850	21820
*Upto 5 Cyc with front loader	13890	16100	18330	20830	23050	25270	27780
5 HT	10120	11730	13350	15180	16790	18410	20240

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 5/18/2024 3:10 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..