

EARTHMAX SR 35 - Technical Specifications



Description

Earthmax SR 35 is a low-profile All Steel radial tire specially designed for articulated dump trucks and wheel loaders. It is ideal for operations requiring exceptional traction and flotation. Earthmax SR 35 provides both excellent traction and stability. Thanks to its strong steel-belted casing, it ensures extraordinary durability and resistance to snags and punctures. The tire is available as cut-resistant compound for a maximum service life even under severe conditions.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Articulated Dump Truck (ADT) • Dozer • Loader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	875/65 R 29 (35/65 R 29)
LI/SS	203 B/214 A2

Dimensions International Standard

TKPH	279
Overall Width (mm)	890
Overall Diameter (mm)	1860
Static Loaded Radius (mm)	816
Rolling Circumference (mm)	5559
Rim Rec	27.00/3.50
Rim Alt	27.00/3.0, 28.00/3.5
Star Rating	**/*
TRA Code	E3/L3

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75
50	14000	14250	15100	15500
10	18500	19500	20600	21200

Printed on 5/18/2024 3:37 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..