

FL 630 ULTRA - Technical Specifications



Description

FL 630 ULTRA is suitable for trailers, tankers and spreaders. Thanks to its reinforced bead and the particular tread design, it is the ideal tire for multipurpose use on any kind of land or on the road. FL 630 ULTRA stands for extraordinarily reduced soil compaction.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Spreader • Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	710/50 R 26.5
LI/SS	170 D/181 A8

Dimensions US Standard

Usa code	94047284
Section Width (inch)	28.6
Overall Diameter (inch)	54.4
Static Loaded Radius (inch)	23.6
Rolling Circumference (inch)	165.7
Rim Rec	AG 24.00
Rim Alt	AG 20.00
ECE	E11-106R-006812

Load capacity (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58
45	3860	4400	4940	6140	6990	8070	9150	10000	10960	12040
40	4230	4830	5420	6750	7670	8860	10050	10980	12040	13230
30	5130	5850	6570	8170	9290	10720	12170	13290	14570	16000
25	5820	6650	7460	9280	10550	12190	13820	15100	16560	18190
15	6690	7640	8580	10660	12120	14010	15880	17350	19020	20900
5	7630	8700	9700	12150	13810	15960	18100	19760	21670	23810

Printed on 5/18/2024 2:39 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..