

# MULTIMAX MP 522 - Technical Specifications



## Description

MULTIMAX MP 522 is the BKT multi-purpose tire developed for agro-industrial applications. It is suitable for all lifting and loading operations on vehicles such as telehandlers and compact loaders. Stability and traction are its strengths as well as outstanding puncture resistance. Thanks to its special compound, MULTIMAX MP 522 has an incredible cut and chip resistance.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Agriculture: Compact Loader • Telehandler

Industrial: Compact Loader • Telehandler

Version	STANDARD
Type	TL
Tyre Size	280/80 R 18 IND (10.5/80 R 18)
LI/SS	132 A8/B

## Dimensions US Standard

Usa code	94045044
Section Width (inch)	11.1
Overall Diameter (inch)	35.7
Static Loaded Radius (inch)	16.6
Rolling Circumference (inch)	108.2
Rim Rec	W 9 ; 9 ; 9 SDC
Rim Alt	W 8 ; W 10
ECE	E11-106R-002962

## Load capacity (lbs)

mph / psi	23	29	35	41	46	51	58	61	64
30	2120	2510	2870	3260	3660	3920	4410	-	-
25	2120	2510	2870	3260	3660	3920	4410	-	-
20	2270	2690	3080	3490	3920	4200	4720	-	-
15	2360	2800	3190	3630	4070	4360	4890	-	-
5 Cyc.	2580	3170	3740	4300	4890	5320	6020	6350	6610
Static	3960	4870	5730	6590	7510	8170	9240	9740	10140

Printed on 5/5/2024 8:04 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..