

MULTIMAX MP 527 - Technical Specifications



Description

MULTIMAX MP 527 is a multi-purpose radial tire designed for telehandlers and compact loaders in agro-industrial applications. The tire shows a block pattern design providing excellent traction even on the harder surfaces. The strong sidewall ensures outstanding stability in lift mode. MULTIMAX MP 527 is made of a special cut-and-chip-resistant compound providing a long service life.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Compact Loader • Telehandler

Industrial: Compact Loader • Telehandler

Version	STANDARD
Type	TL
Tyre Size	360/70 R 18 IND
LI/SS	142 A8/B

Dimensions International Standard

Section Width (mm)	360
Overall Diameter (mm)	969
Static Loaded Radius (mm)	439
Rolling Circumference (mm)	2887
SRI (mm)	475
Rim Rec	11
Rim Alt	W10 ; 11 SDC ; W11 ; 12 ; 12 SDC
ECE	E11-106R-002996

Load capacity (Kg)

km/h / bar	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	1275	1515	1725	1965	2200	2360	2650	-	-
40	1275	1515	1725	1965	2200	2360	2650	-	-
30	1365	1620	1850	2105	2360	2530	2840	-	-
25	1415	1680	1915	2180	2445	2625	2945	-	-
10 Cyc.	1555	1910	2250	2585	2945	3200	3620	3820	3975
Static	2380	2930	3445	3965	4515	4910	5550	5855	6095

Printed on 5/18/2024 4:20 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..