

MULTIMAX MP 527 - Technical Specifications



Description

MULTIMAX MP 527 is a multi-purpose radial tire designed for telehandlers and compact loaders in agro-industrial applications. The tire shows a block pattern design providing excellent traction even on the harder surfaces. The strong sidewall ensures outstanding stability in lift mode. MULTIMAX MP 527 is made of a special cut-and-chip-resistant compound providing and a long service life.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Compact Loader • Telehandler
Industrial: Compact Loader • Telehandler

Version	STANDARD
Type	TL
Tyre Size	400/70 R 24 IND
LI/SS	152 A8/B

Dimensions US Standard

Usa code	94053483
Section Width (inch)	15.9
Overall Diameter (inch)	46.1
Static Loaded Radius (inch)	21.3
Rolling Circumference (inch)	141.6
Rim Rec	13
Rim Alt	DW 12 ; DW 13 ; DW 13 L ; 13 SDC ; DW 14 L
ECE	E11-106R-003958

Load capacity (lbs)

mph / psi	23	29	35	41	46	51	58	61	64
30	3760	4460	5090	5800	6500	6970	7830	-	-
25	3760	4460	5090	5800	6500	6970	7830	-	-
20	4020	4780	5450	6210	6960	7460	8380	-	-
15	4180	4960	5650	6440	7220	7750	8700	-	-
5 Cyc.	4590	5640	6640	7640	8700	9460	10690	11280	11740
Static	7020	8640	10170	11710	13330	14490	16390	17280	18000

Printed on 5/5/2024 5:26 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..