

## RIDEMAX FL 693 M - Technical Specifications



### Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	560/55 R 22.5
LI/SS	162 D

## Dimensions US Standard

Usa code	94067626
Section Width (inch)	21.4
Overall Diameter (inch)	46.5
Static Loaded Radius (inch)	21
Rolling Circumference (inch)	142.3
Rim Rec	AG 16.00
Rim Alt	17.00 ; 20.00
ECE	E11-106R-006972

## Load capacity (lbs)

mph / psi	17	23	29	35	41	46	52	58	65	73
45	3630	4390	4860	5630	6390	7050	7730	8490	9060	9530
40	3980	4820	5350	6180	7020	7750	8490	9330	9950	10470
30	4820	5830	6470	7480	8500	9380	10270	11290	12050	12670
25	5410	6560	7260	8410	9550	10550	11540	12680	13540	14240
15	6290	7620	8440	9770	11090	12250	13400	14730	15720	16540
5	7160	8670	9620	11120	12630	13950	12580	16780	17910	18850

Printed on 5/5/2024 7:09 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..