

# RIDEMAX FL 693 M - Technical Specifications



## Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Agriculture: Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	600/50 R 22.5
LI/SS	159 D/156 E

# Dimensions International Standard

Section Width (mm)	611
Overall Diameter (mm)	1172
Static Loaded Radius (mm)	516
Rolling Circumference (mm)	3574
SRI (mm)	550
Rim Rec	AG 20.00
ECE	E4-106R-000805

## Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1480	1680	2040	2360	2720	3080	3320	3680	4000
65	1620	1840	2235	2585	2975	3370	3635	4025	4375
50	1960	2225	2705	3125	3605	4080	4395	4875	5295
40	2205	2500	3035	3515	4050	4585	4940	5475	5950
25	2560	2905	3530	4080	4705	5325	5740	6365	6915
10	2915	3310	4020	4650	5355	6065	6540	7245	7875

Printed on 5/18/2024 5:38 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..