

RIDEMAX FL 693 M - Technical Specifications



Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	VF 500/50 R 17
LI/SS	156 D

Dimensions International Standard

Section Width (mm)	503
Overall Diameter (mm)	932
Static Loaded Radius (mm)	422
Rolling Circumference (mm)	2880
SRI (mm)	450
Rim Rec	16.00
ECE	E11-106R-007200

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0
70	1095	1385	1675	1860	2150	2440	2695	2950	3240	3460	3640
65	1200	1520	1840	2040	2360	2680	2960	3240	3560	3800	4000
50	1455	1840	2230	2470	2860	3245	3585	3925	4310	4600	4840
40	1635	2070	2505	2775	3210	3645	4030	4410	4845	5170	5440
25	1900	2405	2910	3225	3730	4235	4680	5120	5625	6005	6320
10	2160	2740	3315	3675	4250	4825	5330	5835	6410	6840	7200

Printed on 5/18/2024 3:55 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..