

RIDEMAX IT 697 (M+S) - Technical Specifications



Description

RIDEMAX IT 697 M+S represents the best response to the needs of modern farming contractors during winter operations. It is perfect for haulage and municipality applications. This winter tire for tractors ensures extraordinary grip for all operations on icy and snowy roads without the need of snow chains being mounted. Thanks to the tread grooves and the strong casing, a tractor can be driven in full stability, also at high speed levels. The tread design has been specially developed for heavy-duty services and ensures a low rolling resistance that provides fuel economy plus great stability.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

| | |
|-----------|-----------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 710/70 R 42 IND |
| LI/SS | 180 D/185 A8 |

Dimensions International Standard

| | |
|----------------------------|------------------|
| TKPH | 1 |
| Section Width (mm) | 716 |
| Overall Diameter (mm) | 2068 |
| Static Loaded Radius (mm) | 926 |
| Rolling Circumference (mm) | 6264 |
| SRI (mm) | 975 |
| Rim Rec | DW23 B |
| ECE | 'E11-106R-005178 |

Load capacity (Kg)

| km/h / bar | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 |
|------------|------|------|------|------|------|------|
| 65 | 3760 | 4640 | 5440 | 6320 | 7120 | 8000 |
| 50 | 4060 | 5010 | 5875 | 6825 | 7690 | 8640 |
| 40 | 4350 | 5365 | 6290 | 7310 | 8235 | 9250 |
| 30 | 4510 | 5570 | 6530 | 7585 | 8545 | 9600 |

Printed on 5/5/2024 10:41 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..