



TR 387 - Data Sheet



Description

TR 387 is an agro-industrial tire suitable for sugar cane trailers and compactors. It features high load capacity and is available in different versions to meet specific user requirements in terms of cut and chip resistance, heavy-duty services and durability. The "dual bead" version is particularly suitable for industrial tractors and transport operations using trailers.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Trailer

Industrial: Compactor

| SIZE | Version | USACode | TRA Code | LI/SS | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | ECE |
|-------------------------|----------------------|----------|----------|--------|----|-------------------|------------------------------|------|------|------|-------|------|-----------------|
| 11.2 - 24 | STANDARD | 94066124 | R4 | 112 A8 | | W 10 | W 9 | 11.5 | 42.3 | 19.5 | 127.1 | TL | E11-106R-006420 |
| 18.4 - 26 | HD | 94034086 | R3 | 148 A8 | 16 | DW 16 L | DW 15 L | 19.1 | 57.1 | 25 | 163.4 | TL | |
| 18.4 - 26 | STANDARD | 94004980 | R3 | 138 A8 | 10 | DW 16 L | DW 15 L | 19.1 | 57.1 | 25 | 163.4 | TL | E11-106R-004638 |
| 18.4 - 26 | STANDARD | 94005000 | R3 | 142 A8 | 12 | DW 16 L | DW 15 L | 19.1 | 57.1 | 25 | 163.4 | TL | E4-106R-002718 |
| 23.1 - 26 | DUAL BEAD | 94005130 | R3 | 155 A8 | 16 | DW 20 B | | 23.3 | 61.4 | 27.2 | 184.6 | TL | |
| 23.1 - 26 | DUAL BEAD HD | 94027767 | R3 | 157 A8 | 18 | DW 20 B | | 23.3 | 61.4 | 27.2 | 184.6 | TT | |
| 23.1 - 26 | DUAL BEAD HD | 94030682 | R3 | 157 A8 | 18 | DW 20 B | | 23.3 | 61.4 | 27.2 | 184.6 | TL | |
| 23.1 - 26 | HD | 94005154 | R3 | 162 A8 | 12 | DW 20 B | | 23.3 | 61.4 | 27.2 | 184.6 | TL | E11-106R-003647 |
| 23.1 - 26 | HD DUAL BEAD SPECIAL | 94030941 | R3 | 157 A8 | 18 | DW 20 B | | 23.3 | 61.4 | 27.2 | 184.6 | TL | |
| 23.1 - 26 | STANDARD | 94005048 | R3 | 141 A8 | 8 | DW 20 B | | 23.3 | 61.4 | 27.2 | 184.6 | TL | E11-106R-003595 |
| 23.1 - 26 | STANDARD | 94005079 | R3 | 149 A8 | 12 | DW 20 B | | 23.3 | 61.4 | 27.2 | 184.6 | TL | E4-106R-002317 |
| 23.1 - 26 | STANDARD | 94005116 | R3 | 155 A8 | 16 | DW 20 B | | 23.3 | 61.4 | 27.2 | 184.6 | TL | E4-106R-002318 |
| 12.4 - 28 | STANDARD | 94004959 | R3 | 120 A8 | 8 | W 11 | W 9 ; W 10 | 12.8 | 47.2 | 21.7 | 140.8 | TL | E11-106R-005277 |
| 16.9 - 28 | STANDARD | 94004966 | R3 | 131 A8 | 8 | DW 15 L | DW 14 L | 17.3 | 55.1 | 24.8 | 160.4 | TL | E11-106R-005278 |
| 16.9 - 30 (14 - 30) | STANDARD | 94004973 | R3 | 132 A8 | 8 | DW 15 L | DW 14 L | 17.3 | 57.1 | 25.8 | 166.1 | TL | E11-106R-005279 |
| 18.4 - 30 (15 - 30) | HD | 94005147 | R3 | 147 A8 | 14 | DW 16 L | DW 15 L | 18.7 | 60.2 | 26.8 | 173 | TT | |
| 18.4 - 30 (15 - 30) | STANDARD | 94005024 | R3 | 135 A8 | 8 | DW 16 L | DW 15 L | 18.7 | 60.2 | 26.7 | 177.6 | TL | |
| 620/75 - 30 (23.1 - 30) | DUAL BEAD | 94063956 | R3 | 157 A8 | 16 | DW 20 A ; DW 20 B | | 23.8 | 65.9 | 0 | 0 | TL | |
| 620/75 - 30 (23.1 - 30) | DUAL BEAD HD | 94052868 | R3 | 160 A8 | 18 | DW 20 A ; DW 20 B | | 23.8 | 65.9 | 0 | 0 | TL | |
| 24.5 - 32 | DUAL BEAD HD | 94048854 | R3 | 160 A8 | 16 | DH 21 | DH 21 B ; DH 21 H ; DH 21 HB | 24.6 | 69.1 | 31.1 | 205.7 | TL | |

Printed on 5/19/2024 3:07 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The

user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..