

## V-FLEXA - Data Sheet



### Description

V-FLEXA is a radial tire specifically designed for agricultural trailers. It is a latest-generation flotation product featuring VF technology, which enables the transport of heavy loads both in the fields and on the road with an inflation pressure that is 30% less than that of a standard tire of the same size. Additional steel belts confer major resistance to the casing against impacts. Not only does V-FLEXA support heavy loads in full safety, it also avoids soil compaction thanks to perfect weight distribution. Moreover, V-FLEXA features great self-cleaning properties, durability as well as low rolling resistance.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Trailer

SIZE	Version	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
<b>VF 560/60 R 22.5</b>	STEEL BELTED	166 D			AG 16.00		555	1250	550	3756	600	TL	E11-106R-006763
<b>VF 600/55 R 26.5</b>	STEEL BELTED	167 D			AG20.00		615	1342	580	3986	650	TL	E11-106R-006017
<b>VF 600/65 R 26.5</b>	STEEL BELTED	172 D			AG20.00		615	1453	628	4377	700	TL	E11-106R-006624
<b>VF 650/55 R 26.5</b>	STEEL BELTED	171 D			AG 20.00		644	1389	591	4100	650	TL	E11-106R-006399
<b>VF 710/50 R 26.5</b>	STEEL BELTED	176 D	176 D	176 D	AG 24.00		727	1383	600	4193	650	TL	E11-106R-008833
<b>VF 750/45 R 26.5</b>	STEEL BELTED	176 D	176 D	176 D	AG 24.00		755	1349	585	4095	650	TL	E11-106R-008832
<b>VF 710/50 R 30.5</b>	STEEL BELTED	178 D	178 D	178 D	AG 24.00		727	1485	654	4511	700	TL	E11-106R-008831
<b>VF 750/60 R 30.5</b>	STEEL BELTED	187 D	187 D	187 D	AG 24.00		780	1678	728	5085	800	TL	E11-106R-008147
<b>VF 750/60 R 30.5</b>	STEEL BELTED	187 D	187 D	187 D	AG 24.00		780	1678	728	5085	800	TL	E11-106R-008147

Printed on 5/5/2024 8:43 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..