

XL GRIP (G3) - Technical Specifications



Description

XL GRIP (G-3) is a bias-ply tire for graders designed to minimize cuts and punctures in heavy-duty grading environments where exceptional traction is required.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Grader

Version	STANDARD
Type	TT
Tyre Size	13.00 - 24

Dimensions International Standard

Ply Rating	16
Overall Width (mm)	350
Overall Diameter (mm)	1295
Static Loaded Radius (mm)	601
Rolling Circumference (mm)	3872
Rim Rec	8.00 TG SDC
Rim Alt	9.00/1.5 (DC) ; 10.00/VA SDC
TRA Code	G3

Load capacity (Kg)

km/h / bar	4.00
40	3240

Printed on 5/18/2024 5:31 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..