

TR 675 - Specifiche tecniche



Description

TR 675 è uno pneumatico diagonale appositamente progettato per applicazioni forestali. Il robusto design del rampone offre un'eccellente trazione e autopulizia, mentre la solida struttura della carcassa consente di trasportare carichi pesanti e le sue cinture in acciaio proteggono lo pneumatico da forature e danni. TR 675 presenta una mescola del battistrada resistente al taglio che garantisce un'eccellente resistenza a tagli e scheggiature anche su terreni difficili in condizioni estreme.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Macchina forwarder

Version	STEEL BELTED
Type	TL
Tyre Size	540/65 - 28
LI/SS	155 A8/161 A2

Dimensions US Standard

Usa code	94059959
Ply Rating	16
Section Width (inch)	20.9
Overall Diameter (inch)	56.1
Static Loaded Radius (inch)	26.1
Rolling Circumference (inch)	174.8
Rim Rec	W 16 L
Rim Alt	W 18 L
ECE	E11-106R-005271
TRA Code	LS2

Load capacity (lbs)

mph / psi	48
25	8550

Printed on 19/05/2024 18:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..