

## TR 675 - Scheda tecnica



### Description

TR 675 è uno pneumatico diagonale appositamente progettato per applicazioni forestali. Il robusto design del rampone offre un'eccellente trazione e autopulizia, mentre la solida struttura della carcassa consente di trasportare carichi pesanti e le sue cinture in acciaio proteggono lo pneumatico da forature e danni. TR 675 presenta una mescola del battistrada resistente al taglio che garantisce un'eccellente resistenza a tagli e scheggiature anche su terreni difficili in condizioni estreme.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Macchina forwarder

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
540/65 - 28	STEEL BELTED	LS2	155 A8/161 A2	16	W 16 L	W 18 L	530	1425	663	4440	TL	E11-106R-005271

Printed on 19/05/2024 05:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..