

AGRIMAX RT 600 - Technical Specifications

Description

AGRIMAX RT 600 is the ideal tire for grassland, harvesting and spreading applications. Thanks to its large contact area, AGRIMAX RT 600 ensures an excellent pressure distribution on the land reducing damage on grassland and protecting your soil. Thanks to its round shoulder technology, the reinforced bead and increased number of lugs, it guarantees great stability and traction.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Harvester • Spreader • Tractor



Version	STEEL BELTED
Type	TL
Tyre Size	IF 710/75 R 34 CFO
LI/SS	184A8/B

Dimensions International Standard

Section Width (mm)	715
Overall Diameter (mm)	1920
Static Loaded Radius (mm)	856
Rolling Circumference (mm)	5771
SRI (mm)	900
Rim Rec	DW25 B
Rim Alt	DW23 B
ECE	E11-106R-0010577

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
50	3510	4140	4770	5310	5940	6480	7110	7650	8370	9000
40	3510	4140	4770	5310	5940	6480	7110	7650	8370	9000
30	3655	4310	4965	5525	6180	6740	7395	7960	8705	9360
10	4460	5260	6060	6745	7545	8230	9030	9720	10630	11430
Upto 30 Cyc	4565	5385	6205	6905	7725	8425	9245	9945	10885	11700
Upto 15 Cyc	5445	6420	7395	8235	9210	10045	11025	11860	12975	13950
Upto 10 Cyc	5970	7040	8110	9030	10100	11020	12090	13005	14230	15300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/21/2024 7:40 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..