

SKID POWER - Technische Daten



Description

SKID POWER wurde für Skid-Steer-Lader bei Anwendungen im Baugewerbe entworfen. Er bietet ausgezeichnete Traktion und zeichnet sich durch verbesserte Selbstreinigung aus. Der Reifen glänzt mit einer extra tiefen Lauffläche und zusätzlichem Flankenschutz, die ausgezeichnete Schnitt- und Reißfestigkeit sowie erstklassige Beständigkeit verleihen. SKID POWER ist der ideale Reifen auf lockerem Untergrund.

UM

International Standard

Construction

 BIAS

Machinery

Industrie: Skid-Steer-Lader

Version	IMPLEMENT
Type	TL
Tyre Size	23 X 10.5 - 12
LI/SS DRIVE WHEEL	90 A8
LI/SS FREE ROLLING	90 A8

Dimensions International Standard

Ply Rating	6
Section Width (mm)	264
Overall Diameter (mm)	590
Rim Rec	8.5 I - 55
Rim Alt	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-008809

Load capacity (Kg)

km/h / bar	2.80
40 FR	600
40 DW	600

Printed on 27.07.2024 13:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..