

FORESTMAX - Technical Specifications



Description

FORESTMAX is BKT's new radial tire for tractors, which has been mainly developed for forestry applications, but can also be employed for some specific farming operations such as soil milling and stone breaking.

Its multi-ply polyester casing and the reinforced sidewall are designed to withstand the harsh forestry operating conditions. In addition, the cut-and-chip-resistant tread compound and the steel-belted structure significantly minimize the risk of punctures in the woodland. The tire features a robust open shoulder providing best traction and top stability even on rugged and uneven terrains. The combination of tread resistance and the particular shoulder design stand for optimum self-cleaning properties along with a long tire life making FORESTMAX your ideal partner in the forest.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

Version	STEEL BELTED
Type	TL
Tyre Size	600/60R28
LI/SS	152A8/149B

Dimensions US Standard

Usa code	94512850
Section Width (inch)	22.4
Overall Diameter (inch)	56.3
Static Loaded Radius (inch)	25.8
Rolling Circumference (inch)	169.9
Rim Rec	DW18L
Rim Alt	DW20B
ECE	E11-106R-0010523

Load capacity (lbs)

mph / psi	17	20	23	26	29	32	35
30	4870	5450	5590	6160	6660	6880	7160
25	5320	5950	6110	6730	7270	7520	7830
20	5700	6370	6540	7210	7790	8050	8380
15	5920	6610	6790	7480	8090	8360	8700
12	6560	7330	7520	8290	8960	9260	9630
10	7140	7980	8190	9030	9750	10070	10490
5	7990	8930	9160	10100	10910	11280	11740
5 forestry service	-	-	-	-	-	-	9630
0 forestry service	-	-	-	-	-	-	18000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/01/2025 14:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..